

Transition Metal Mobility and Recovery from Weathered Serpentine and Serpentine Skarn Tailings from Lord Brassey Mine, Australia and Record Ridge, British Columbia, Canada

MJ Honda-McNeil^a, SA Wilson^a, BF Millili^b, N Zeyen^a, B Wang^a, CC Turvey^c, CJ Vessey^a, AS Patel^a, AJ Locock^a, JL Hamilton^d, DJ Paterson^d, G Southam^e, JT Poitras^e, TR Jones^e, and SM Jowitt^f

^a *Department of Earth and Atmospheric Sciences, University of Alberta, Edmonton, AB T6G 2E3, Canada*

^b *BHP, 171 Collins Street, Melbourne, VIC 3000, Australia*

^c *Bradshaw Research Initiative for Minerals & Mining, The University of British Columbia, Vancouver, BC, Canada*

^d *Australian Synchrotron, Melbourne, VIC 3168, Australia*

^e *School of Earth & Environmental Sciences, The University of Queensland, Brisbane, Qld 4072, Australia*

^f *Department of Geoscience, University of Nevada, Las Vegas, NV, USA*

As mineral resources become scarcer, companies are lowering their ore cut-off grades and resorting to exploring deeper underground and in more isolated areas. Incorporating tailings storage facilities and tailings reprocessing as part of the ore processing circuit can potentially extend the lives of mines and save on future exploration costs. Ultramafic and mafic mine tailings host resources including first and second row transition metals, such as nickel (Ni), cobalt (Co), and platinum group elements (PGE), whose high value and recovery could serve as a motivator for existing mines to reprocess their tailings. Many of these target metals are initially hosted by olivine, are repartitioned during serpentinization to form sulfides, oxides and alloys, and then are remobilized during weathering to form authigenic carbonates, sulfates and oxyhydroxides. Reprocessing tailings may further provide environmental benefits, including a reduction in waste output and the ability to offset greenhouse gas emissions by enhanced silicate-weathering and carbonation reactions. Here we use powder X-ray diffraction, scanning electron microscopy, electron probe micro-analysis and synchrotron X-ray fluorescence mapping to demonstrate how first and second row transition metals are mobilized to their final sinks. Samples of serpentine, skarn and weathered tailings from the historical Lord Brassey nickel mine in Tasmania, Australia and weathered outcrops of serpentine ore from the proposed magnesium mine in Record Ridge, BC, Canada are analyzed and compared. Preliminary results from these climatically similar localities indicate clear transition metal dissemination patterns across alteration zones and distinct partitioning behavior (ex. homogenous distribution of Ni within sulfides) in weathering products. By developing an understanding of the sinks for metals across the mining lifecycle, we aim to cultivate an economically viable framework for tailings reprocessing that capitalizes on metal mobility during tailings weathering.

Corresponding author: hondamcn@ualberta.ca